

BYA CE standard lace up cheville bottes de sécurité en pvc

Nom du produit:	Avoir des bottes de sécurité pvc de cheville en dentelle de certificat de la CE
Numéro d'article:	PAR UN
Color:	Tige noire avec semelle jaune
Taille:	38-46 (4-12)
Poids moyen:	1,8 kg / p (avec embout d'acier et plaque d'acier)
Matériel:	Tige en PVC et semelle en PVC
Doublure:	Polyester facilement séché
Construction:	Injection de PVC
la norme	Conforme à la norme CE EN ISO 20345 (avec embout d'acier et plaques d'acier)
Protection des orteils en acier	Rencontrez 200 Joule
Protection des orteils en acier	Rencontrez 1500 Newton
Résistant à la perforation	Rencontrez 1100 Newton
Caractéristiques	1. Bottes en caoutchouc résistant à l'eau / acide / alcali / huile / graisse, anti-dérapant et antistatique. 2. L'orteil en acier peut être Impact & ampère; ampère; résistant à la compression. 3. la plaque d'acier peut être résistante à la perforation. 4. Semelle extérieure est résistant à l'abrasion et contrat. 5. Protection de cheville, absorption d'énergie sur la région de siège de talon, renforçant l'orteil et le talon 6. résistant aux basses températures.
Garantie:	5 mois, qualité robuste et solide.
Paquet:	1 paire par poly sac, 10 paires par carton
Taille de carton:	59x31x31cm
G.W./N.W .:	18KGS / 16KGS
UNEMont de conteneurs de chargement:	5000 paires / conteneur 1x20 ' 10000 paires / conteneur 1x40 ' 11000 paires / HQ conteneur 1x40 'HQ
Temps d'échantillonnage:	Dans 1 semaine
Charge de l'échantillon:	un échantillon de la paire est gratuit, le client doit payer les frais de transport.

BYA cheville bottes de pluie:



Machine d'Inection:



**Automatic Injection
Molding Machine**



**Puncture
Testing Machine**



**Impact Resistant
Testing Machine**



**Tensile
testing machine**

Certificat CE:

EC Type Examination Certificate



Approved Body 0362

The safety footwear detailed herein meets the criteria of an EC Type Examination in accordance with Article 10 of the PPE Directive (89/685/EEC) including amendments and corrigendum up to 14/12/2010 for intermediate design category products.

This has been shown through satisfactory testing to EN ISO 20345: 2011 and examination of the Technical File Documentation.

Following an EC Declaration of Product Conformity you are hereby licensed to mark the product(s) detailed in accordance with Article 13 of the PPE Directive (89/685/EEC).

ITS Testing Services (UK) Ltd
Centre Court
Meridian Business Park
Leicester, LE19 1WD
United Kingdom
Phone: +44 (0)116 263 0330
Fax: +44 (0)116 263 0311



www.intertek.com

Issued to	: HARBIN ANA SAFETY PRODUCTS MFG. CO., LTD. LIXIN VILLAGE, XINHUA TOWN, ACHENG DISTRICT, HARBIN, HEILONGJIANG PROVINCE, CHINA	
Authorised Representative	: HEILONGJIANG SAFER CO., LTD. RM502 PUFA PLAZA, NO. 209 CHANGJIANG RD., HARBIN, CHINA	
Manufacturer	: HARBIN ANA SAFETY PRODUCTS MFG. CO., LTD. LIXIN VILLAGE, XINHUA TOWN, ACHENG DISTRICT, HARBIN, HEILONGJIANG PROVINCE, CHINA	
Date of Issue	: 26 May 2015	
Expiry Date	: 26 May 2020	
Certificate No.	: LEC FI00348759	
Product Reference(s)	: BBA (FW45) SAFETY BOOTS	
Description	: Construction	: INJECTION
	: Toecap	: 459 STEEL TOECAP
	: Midsole	: OY# 160 STEEL PLATE
	: Last	: HA-459
	: Sole	: PVC & NITRILE
	: Mould	: HA-A
	: Test Report(s)	: GZHT90504071, GZHT90391794
	: Size Range	: EUR 38-47
	: Category	: S5 SRA

Carroll
Authorised

26/05/2015

Date

P. Williams
Certification Manager

26/05/2015

Date

For and on behalf of ITS Testing Services (UK) Limited

Registered in England No. 1107024 Registered Office: Academy Place, 1-3 Brook Street, Bournemouth, Dorset, BH1 1TQ

This certificate is for the exclusive use of Intertek's Client and is provided pursuant to the Distribution Agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party other than to the Client in accordance with the agreement. For any loss, damage or personal consequence to the use of this Certificate, only the Client is authorised to permit copying or reproduction of this Certificate and then only in its entirety. Use of Intertek's Certificate when it is restricted to the certificate set out in this agreement and in this Certificate. Any further use of the Intertek name for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek.

