

BBA zwarte enkel pvc-veiligheidsschoenen met stalen neus

Productnaam:	Heb Ce-certificaat zwarte enkel pvc veiligheidsschoenen met stalen neus
Item nr:	BBA
Color:	Zwart bovenwerk met zwarte zool
Grootte:	38-46 (4-12)
Gemiddeld gewicht:	1,8 kg / pr (met stalen neus en stalen plaat)
materiaal:	PVC-bovenwerk en PVC-zool
Voering:	Gemakkelijk gedroogd polyester
Bouw:	PVC-injectie
Standaard	Voldoet aan de norm CE EN ISO 20345 (met stalen neus en stalen platen)
Stalen teenbescherming	Maak kennis met 200 Joule
Stalen teenbescherming	Ontmoet 1500 Newton
Lekbestendig	Ontmoet 1100 Newton
Kenmerken	1. Water / Zuur / Alkali / olie / vetbestendig, antislip, antistatische rubberen laarzen. 2. Stalen neus kan Impact & & bestand tegen compressie. 3. stalen plaat kan lekbestendig zijn. 4. buitenzool is slijtvast en contract. 5. Enkelbescherming, energieabsorptie op het hielzittingsgebied, versterkende teen en hiel 6. bestendig bij lage temperaturen.
Garantie:	5 maanden, robuuste en solide kwaliteit.
Pakket:	1 paar per polyzak, 10 paar per doos
Karton grootte:	59x31x31cm
G.W./N.W .:	18KGS / 16KGS
EENmontage van laadcontainers:	5000 paar / container 1x20 ' 10000 paar / container 1x40 ' 11000 paar / HQ container 1x40 'HQ
Proeftijd:	Binnen 1 week
Monster lading:	een paar monster is gratis, klant moet de vrachtkosten betalen.

BBA enkel PVC-veiligheidsschoenen:

CE



Injection machine:



**Automatic Injection
Molding Machine**



**Puncture
Testing Machine**



**Impact Resistant
Testing Machine**



**Tensile
testing machine**

CE-certificaat:

EC Type Examination Certificate



Approved Body 0362

The safety footwear detailed herein meets the criteria of an EC Type Examination in accordance with Article 10 of the PPE Directive (89/685/EEC) including amendments and corrigendum up to 14/12/2010 for intermediate design category products.

This has been shown through satisfactory testing to EN ISO 20345: 2011 and examination of the Technical File Documentation.

Following an EC Declaration of Product Conformity you are hereby licensed to mark the product(s) detailed in accordance with Article 13 of the PPE Directive (89/685/EEC).

ITS Testing Services (UK) Ltd
Centre Court
Meridian Business Park
Leicester, LE19 1WD
United Kingdom
Phone: +44 (0)116 263 0330
Fax: +44 (0)116 263 0311



www.intertek.com

Issued to	: HARBIN ANA SAFETY PRODUCTS MFG. CO., LTD. LIXIN VILLAGE, XINHUA TOWN, ACHENG DISTRICT, HARBIN, HEILONGJIANG PROVINCE, CHINA	
Authorised Representative	: HEILONGJIANG SAFER CO., LTD. RM502 PUFA PLAZA, NO. 209 CHANGJIANG RD., HARBIN, CHINA	
Manufacturer	: HARBIN ANA SAFETY PRODUCTS MFG. CO., LTD. LIXIN VILLAGE, XINHUA TOWN, ACHENG DISTRICT, HARBIN, HEILONGJIANG PROVINCE, CHINA	
Date of Issue	: 26 May 2015	
Expiry Date	: 26 May 2020	
Certificate No.	: LEC FI00348759	
Product Reference(s)	: BBA (FW45) SAFETY BOOTS	
Description	: Construction	: INJECTION
	: Toecap	: 459 STEEL TOECAP
	: Midsole	: OY# 160 STEEL PLATE
	: Last	: HA-459
	: Sole	: PVC & NITRILE
	: Mould	: HA-A
	: Test Report(s)	: GZHT90504071, GZHT90391794
	: Size Range	: EUR 38-47
	: Category	: S5 SRA

Carroll
Authorised

26/05/2015

Date

P. Williams
Certification Manager

26/05/2015

Date

For and on behalf of ITS Testing Services (UK) Limited

Registered in England No. 1107024 Registered Office: Academy Place, 1-3 Brook Street, Bournemouth, Dorset, BH1 1TQ

This certificate is for the exclusive use of Intertek's Client and is provided pursuant to the Distribution Agreement between Intertek and its Client. Intertek's endorsement and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party other than to the Client in accordance with the agreement. For any loss, damage or personal consequence to the use of this Certificate, only the Client is authorised to permit copying or reproduction of this Certificate and then only in its entirety. Use of Intertek's Certificate when it is restricted to the conditions set out in this agreement and in this Certificate. Any further use of the Intertek name for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek.

