

## GYA groene enkel pvc werklaarzen met stalen neus

|                                |                                                                                                                                                                                                                                                                                                                                                                                |
|--------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Productnaam:                   | Heb enkelwerkende pvc-werklaarzen met stalen neus en CE-certificaat                                                                                                                                                                                                                                                                                                            |
| Item nr:                       | GYA                                                                                                                                                                                                                                                                                                                                                                            |
| Color:                         | Groen bovenwerk met gele zool                                                                                                                                                                                                                                                                                                                                                  |
| Grootte:                       | 38-46 (4-12)                                                                                                                                                                                                                                                                                                                                                                   |
| Gemiddeld gewicht:             | 1,8 kg / pr (met stalen neus en stalen plaat)                                                                                                                                                                                                                                                                                                                                  |
| materiaal:                     | PVC-bovenwerk en PVC-zool                                                                                                                                                                                                                                                                                                                                                      |
| Voering:                       | Gemakkelijk gedroogd polyester                                                                                                                                                                                                                                                                                                                                                 |
| Bouw:                          | PVC-injectie                                                                                                                                                                                                                                                                                                                                                                   |
| Standaard                      | Voldoet aan de norm CE EN ISO 20345 (met stalen neus en stalen platen)                                                                                                                                                                                                                                                                                                         |
| Stalen teenbescherming         | Maak kennis met 200 Joule                                                                                                                                                                                                                                                                                                                                                      |
| Stalen teenbescherming         | Ontmoet 1500 Newton                                                                                                                                                                                                                                                                                                                                                            |
| Lekbestendig                   | Ontmoet 1100 Newton                                                                                                                                                                                                                                                                                                                                                            |
| Kenmerken                      | 1. Water / Zuur / Alkali / olie / vetbestendig, antislip, antistatische rubberen laarzen.<br>2. Stalen neus kan Impact & & bestand tegen compressie.<br>3. stalen plaat kan lekbestendig zijn.<br>4. buitenzool is slijtvast en contract.<br>5. Enkelbescherming, energieabsorptie op het hielzittingsgebied, versterkende teen en hiel<br>6. bestendig bij lage temperaturen. |
| Garantie:                      | 5 maanden, robuuste en solide kwaliteit.                                                                                                                                                                                                                                                                                                                                       |
| Pakket:                        | 1 paar per polyzak, 10 paar per doos                                                                                                                                                                                                                                                                                                                                           |
| Karton grootte:                | 59x31x31cm                                                                                                                                                                                                                                                                                                                                                                     |
| G.W./N.W .:                    | 18KGS / 16KGS                                                                                                                                                                                                                                                                                                                                                                  |
| EENmontage van laadcontainers: | 5000 paar / container 1x20 '<br>10000 paar / container 1x40 '<br>11000 paar / HQ container 1x40 'HQ                                                                                                                                                                                                                                                                            |
| Proeftijd:                     | Binnen 1 week                                                                                                                                                                                                                                                                                                                                                                  |
| Monster lading:                | een paar monster is gratis, klant moet de vrachtkosten betalen.                                                                                                                                                                                                                                                                                                                |

## GYA enkelwerk regenlaarzen:



**Injection machine:**



**Automatic Injection  
Molding Machine**



**Puncture  
Testing Machine**



**Impact Resistant  
Testing Machine**



**Tensile  
testing machine**

**CE-certificaat:**

# EC Type Examination Certificate



## Approved Body 0362

The safety footwear detailed herein meets the criteria of an EC Type Examination in accordance with Article 10 of the PPE Directive (89/685/EEC) including amendments and corrigendum up to 14/12/2010 for intermediate design category products.

This has been shown through satisfactory testing to EN ISO 20345: 2011 and examination of the Technical File Documentation.

Following an EC Declaration of Product Conformity you are hereby licensed to mark the product(s) detailed in accordance with Article 13 of the PPE Directive (89/685/EEC).

ITS Testing Services (UK) Ltd  
Centre Court  
Meridian Business Park  
Leicester, LE19 1WD  
United Kingdom  
Phone: +44 (0)116 263 0330  
Fax: +44 (0)116 263 0311



[www.intertek.com](http://www.intertek.com)

|                                  |                                                                                                                                     |                              |
|----------------------------------|-------------------------------------------------------------------------------------------------------------------------------------|------------------------------|
| <b>Issued to</b>                 | : HARBIN ANA SAFETY PRODUCTS MFG. CO., LTD.<br>LIXIN VILLAGE, XINHUA TOWN, ACHENG DISTRICT,<br>HARBIN, HEILONGJIANG PROVINCE, CHINA |                              |
| <b>Authorised Representative</b> | : HEILONGJIANG SAFER CO., LTD.<br>RM502 PUFA PLAZA, NO. 209 CHANGJIANG RD., HARBIN,<br>CHINA                                        |                              |
| <b>Manufacturer</b>              | : HARBIN ANA SAFETY PRODUCTS MFG. CO., LTD.<br>LIXIN VILLAGE, XINHUA TOWN, ACHENG DISTRICT,<br>HARBIN, HEILONGJIANG PROVINCE, CHINA |                              |
| <b>Date of Issue</b>             | : 26 May 2015                                                                                                                       |                              |
| <b>Expiry Date</b>               | : 26 May 2020                                                                                                                       |                              |
| <b>Certificate No.</b>           | : LEC FI00348759                                                                                                                    |                              |
| <b>Product Reference(s)</b>      | : BBA (FW45)<br>SAFETY BOOTS                                                                                                        |                              |
| <b>Description</b>               | : Construction                                                                                                                      | : INJECTION                  |
|                                  | : Toecap                                                                                                                            | : 459 STEEL TOECAP           |
|                                  | : Midsole                                                                                                                           | : OY# 160 STEEL PLATE        |
|                                  | : Last                                                                                                                              | : HA-459                     |
|                                  | : Sole                                                                                                                              | : PVC & NITRILE              |
|                                  | : Mould                                                                                                                             | : HA-A                       |
|                                  | : Test Report(s)                                                                                                                    | : GZHT90504071, GZHT90391794 |
|                                  | : Size Range                                                                                                                        | : EUR 38-47                  |
|                                  | : Category                                                                                                                          | : S5 SRA                     |

*Carroll*  
Authorised

26/05/2015

Date

*P. Williams*  
Certification Manager

26/05/2015

Date

For and on behalf of ITS Testing Services (UK) Limited

Registered in England No. 1107024 Registered Office: Academy Place, 1-3 Brook Street, Bournemouth, Dorset, BH1 1TQ

This certificate is for the exclusive use of Intertek's Client and is provided pursuant to the Distribution Agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party other than to the Client in accordance with the agreement. For any loss, damage or personal consequence to the use of this Certificate, only the Client is authorised to permit copying or reproduction of this Certificate and then only in its entirety. Use of Intertek's Certificate when it is restricted to the certificate set out in this agreement and in this Certificate. Any further use of the Intertek name for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek.

