BBA black ankle pvc safety shoes with steel toe

Product Name: Have CE certificate black ankle pvc safety shoes with steel toe Item No: BBA Color: Black upper with black sole Size: 38-46 (4-12) Average weight: 1.8 kgs/pr (with steel toe and steel plate) material: PVC upper and PVC sole Lining: Easily dried polyester Construction: PVC injection Standard Meet CE EN ISO 20345 standard (with steel toe and steel plates) Steel Toe Protection Meet 200 Joule Steel Toe Protection Meet 1500 Newton Puncture Resistant Meet 1100 Newton Lining: Lining: Meet 1100 Newton Puncture Resistant Meet 1100 Newton Lining: Lin		
Color: Black upper with black sole Size: 38-46 (4-12) Average weight: 1.8 kgs/pr (with steel toe and steel plate) material: PVC upper and PVC sole Lining: Easily dried polyester Construction: PVC injection Standard Meet CE EN ISO 20345 standard (with steel toe and steel plates) Steel Toe Protection Meet 200 Joule Steel Toe Protection Meet 1500 Newton Puncture Resistant Meet 1100 Newton 1. Water / Acid / Alkali / oil / grease resistant, non-slip, anti-static rubber boots. 2. Steel toe can be Impact & amp; amp; compression resistant. 3. steel plate can be puncture resistant. 4. outsole is abrasion resistant and Contract. 5. Ankle protection, energy absorption on the heel seat region, strengthening toe and heel for resistant at low temperatures. Guarantee: 5 months, robust and solid quality. Package: 1 pair per poly bag, 10 pairs per carton Carton Size: 59x31x31cm G.W./N.W.: 18KGS/ 16KGS Amount of load containers: 18KGS/ 16KGS Soul pairs / container 1x40 ' HQ Sample time: Within 1 week	Product Name:	Have CE certificate black ankle pvc safety shoes with steel toe
Size: 38-46 (4-12) Average weight: 1.8 kgs/pr (with steel toe and steel plate) material: PVC upper and PVC sole Lining: Easily dried polyester Construction: PVC injection Standard Meet CE EN ISO 20345 standard (with steel toe and steel plates) Steel Toe Protection Meet 200 Joule Steel Toe Protection Meet 1500 Newton Puncture Resistant Meet 1100 Newton Characteristics Newtor / Acid / Alkali / oil / grease resistant, non-slip, anti-static rubber boots. 2. Steel toe can be Impact & amp; amp; compression resistant. 3. steel plate can be puncture resistant. 4. outsole is abrasion resistant and Contract. 5. Ankle protection, energy absorption on the heel seat region, strengthening toe and heel 6. resistant at low temperatures. Guarantee: 5 months, robust and solid quality. Package: 1 pair per poly bag, 10 pairs per carton Carton Size: 59x31x31cm G.W./N.W.: 18KGS/16KGS 5000 pairs / container 1x20 ' 10000 pairs / container 1x40 ' 11000 pairs / HQ container 1x40 '	Item No:	BBA
Average weight: 1.8 kgs/pr (with steel toe and steel plate) material: PVC upper and PVC sole Lining: Easily dried polyester Construction: PVC injection Standard Meet CE EN ISO 20345 standard (with steel toe and steel plates) Steel Toe Protection Meet 200 Joule Steel Toe Protection Meet 1500 Newton Puncture Resistant Meet 1100 Newton L. Water / Acid / Alkali / oil / grease resistant, non-slip, anti-static rubber boots. 2. Steel toe can be Impact & amp; amp; compression resistant. 3. steel plate can be puncture resistant. 4. outsole is abrasion resistant and Contract. 5. Ankle protection, energy absorption on the heel seat region, strengthening toe and heel 6. resistant at low temperatures. Guarantee: 5 months, robust and solid quality. Package: 1 pair per poly bag, 10 pairs per carton Carton Size: 59x31x31cm G.W./N.W.: 18KGS/ 16KGS 5000 pairs / container 1x40 ' 10000 pairs / container 1x40 ' 11000 pairs / HQ container 1x40 ' HQ Sample time: Within 1 week	Color:	Black upper with black sole
material: Lining: Easily dried polyester Construction: PVC injection Standard Meet CE EN ISO 20345 standard (with steel toe and steel plates) Steel Toe Protection Meet 200 Joule Steel Toe Protection Meet 1500 Newton Puncture Resistant Meet 1100 Newton 1. Water / Acid / Alkali / oil / grease resistant, non-slip, anti-static rubber boots. 2. Steel toe can be Impact & amp; amp; compression resistant. 3. steel plate can be puncture resistant. 4. outsole is abrasion resistant and Contract. 5. Ankle protection, energy absorption on the heel seat region, strengthening toe and heel 6. resistant at low temperatures. Guarantee: 5 months, robust and solid quality. Package: 1 pair per poly bag, 10 pairs per carton Carton Size: 59x31x31cm G.W./N.W.: 18KGS/ 16KGS Amount of load containers: 5000 pairs / container 1x20 ' 10000 pairs / container 1x40 ' 11000 pairs / HQ container 1x40 '	Size:	38-46 (4-12)
Lining: Easily dried polyester Construction: PVC injection Standard Meet CE EN ISO 20345 standard (with steel toe and steel plates) Steel Toe Protection Meet 200 Joule Steel Toe Protection Meet 1500 Newton Puncture Resistant Meet 1100 Newton Characteristics 1. Water / Acid / Alkali / oil / grease resistant, non-slip, anti-static rubber boots. 2. Steel toe can be Impact & amp; amp; compression resistant. 3. steel plate can be puncture resistant. 4. outsole is abrasion resistant and Contract. 5. Ankle protection, energy absorption on the heel seat region, strengthening toe and heel 6. resistant at low temperatures. Guarantee: 5 months, robust and solid quality. Package: 1 pair per poly bag, 10 pairs per carton Carton Size: 59x31x31cm G.W./N.W.: 18KGS/ 16KGS Amount of load containers: 5000 pairs / container 1x20 ' 10000 pairs / container 1x40 ' 11000 pairs / HQ container 1x40 ' 11000 pairs / Within 1 week	Average weight:	1.8 kgs/pr (with steel toe and steel plate)
Construction: PVC injection Standard Meet CE EN ISO 20345 standard (with steel toe and steel plates) Steel Toe Protection Meet 200 Joule Steel Toe Protection Meet 1500 Newton Puncture Resistant Meet 1100 Newton 1. Water / Acid / Alkali / oil / grease resistant, non-slip, anti-static rubber boots. 2. Steel toe can be Impact & amp; amp; compression resistant. 4. outsole is abrasion resistant and Contract. 5. Ankle protection, energy absorption on the heel seat region, strengthening toe and heel 6. resistant at low temperatures. Guarantee: 5 months, robust and solid quality. Package: 1 pair per poly bag, 10 pairs per carton Carton Size: 59x31x31cm G.W./N.W.: 18KGS/ 16KGS Amount of load containers: 5000 pairs / container 1x20 ' 10000 pairs / container 1x40 ' 11000 pairs / HQ container 1x40 ' HQ Sample time: Within 1 week	material:	PVC upper and PVC sole
Standard Meet CE EN ISO 20345 standard (with steel toe and steel plates) Steel Toe Protection Meet 1500 Newton Puncture Resistant Meet 1100 Newton L. Water / Acid / Alkali / oil / grease resistant, non-slip, anti-static rubber boots. Steel plate can be Impact & amp; amp; compression resistant. Steel plate can be puncture resistant. Steel plate can be puncture resistant. Susteel plate can be puncture	Lining:	Easily dried polyester
Steel Toe Protection Meet 200 Joule Steel Toe Protection Meet 1500 Newton Puncture Resistant Meet 1100 Newton Characteristics 1. Water / Acid / Alkali / oil / grease resistant, non-slip, anti-static rubber boots. 2. Steel toe can be Impact & amp; amp; compression resistant. 3. steel plate can be puncture resistant. 4. outsole is abrasion resistant and Contract. 5. Ankle protection, energy absorption on the heel seat region, strengthening toe and heel 6. resistant at low temperatures. Guarantee: 5 months, robust and solid quality. Package: 1 pair per poly bag, 10 pairs per carton Carton Size: 59x31x31cm G.W./N.W.: 18KGS/ 16KGS Amount of load containers: 5000 pairs / container 1x20 ' 10000 pairs / container 1x40 ' 11000 pairs / HQ container 1x40 ' HQ Sample time: Within 1 week	Construction:	PVC injection
Steel Toe Protection Meet 1500 Newton Puncture Resistant Meet 1100 Newton Characteristics 1. Water / Acid / Alkali / oil / grease resistant, non-slip, anti-static rubber boots. 2. Steel toe can be Impact & amp; amp; compression resistant. 3. steel plate can be puncture resistant. 4. outsole is abrasion resistant and Contract. 5. Ankle protection, energy absorption on the heel seat region, strengthening toe and heel 6. resistant at low temperatures. Guarantee: 5 months, robust and solid quality. Package: 1 pair per poly bag, 10 pairs per carton Carton Size: 59x31x31cm G.W./N.W.: 18KGS/ 16KGS Amount of load containers: 5000 pairs / container 1x20 ' 10000 pairs / container 1x40 ' 11000 pairs / HQ container 1x40 ' HQ Sample time: Within 1 week	Standard	Meet CE EN ISO 20345 standard (with steel toe and steel plates)
Puncture Resistant Meet 1100 Newton 1. Water / Acid / Alkali / oil / grease resistant, non-slip, anti-static rubber boots. 2. Steel toe can be Impact & amp; amp; compression resistant. 3. steel plate can be puncture resistant. 4. outsole is abrasion resistant and Contract. 5. Ankle protection, energy absorption on the heel seat region, strengthening toe and heel 6. resistant at low temperatures. Guarantee: 5 months, robust and solid quality. Package: 1 pair per poly bag, 10 pairs per carton Carton Size: 59x31x31cm G.W./N.W.: 18KGS/ 16KGS Amount of load containers: 5000 pairs / container 1x20 ' 10000 pairs / container 1x40 ' 11000 pairs / HQ container 1x40 ' 11000 pairs / HQ container 1x40 ' HQ Sample time: Within 1 week	Steel Toe Protection	Meet 200 Joule
1. Water / Acid / Alkali / oil / grease resistant, non-slip, anti-static rubber boots. 2. Steel toe can be Impact & amp; amp; compression resistant. 3. steel plate can be puncture resistant. 4. outsole is abrasion resistant and Contract. 5. Ankle protection, energy absorption on the heel seat region, strengthening toe and heel 6. resistant at low temperatures. Guarantee: 5 months, robust and solid quality. Package: 1 pair per poly bag, 10 pairs per carton Carton Size: 59x31x31cm G.W./N.W.: 18KGS/ 16KGS Amount of load containers: 5000 pairs / container 1x20 ' 10000 pairs / container 1x40 ' 11000 pairs / HQ container 1x40 ' HQ Sample time: Within 1 week	Steel Toe Protection	Meet 1500 Newton
2. Steel toe can be Impact & amp; amp; compression resistant. 3. steel plate can be puncture resistant. 4. outsole is abrasion resistant and Contract. 5. Ankle protection, energy absorption on the heel seat region, strengthening toe and heel 6. resistant at low temperatures. Guarantee: 5 months, robust and solid quality. Package: 1 pair per poly bag, 10 pairs per carton Carton Size: 59x31x31cm G.W./N.W.: 18KGS/ 16KGS Amount of load containers: 5000 pairs / container 1x20 ' 10000 pairs / container 1x40 ' 11000 pairs / HQ container 1x40 ' HQ Sample time: Within 1 week	Puncture Resistant	Meet 1100 Newton
Package: 1 pair per poly bag, 10 pairs per carton Carton Size: 59x31x31cm G.W./N.W.: 18KGS/ 16KGS Amount of load containers: 5000 pairs / container 1x20 ' 10000 pairs / container 1x40 ' 11000 pairs / HQ container 1x40 ' HQ Sample time: Within 1 week	Characteristics	 Steel toe can be Impact & amp; amp; compression resistant. steel plate can be puncture resistant. outsole is abrasion resistant and Contract. Ankle protection, energy absorption on the heel seat region, strengthening toe and heel
Carton Size: 59x31x31cm G.W./N.W.: 18KGS/ 16KGS Amount of load containers: 5000 pairs / container 1x20 ' 10000 pairs / container 1x40 ' 11000 pairs / HQ container 1x40 ' HQ Sample time: Within 1 week	Guarantee:	5 months, robust and solid quality.
G.W./N.W.: 18KGS/ 16KGS Amount of load containers: 5000 pairs / container 1x20 ' 10000 pairs / container 1x40 ' 11000 pairs / HQ container 1x40 ' HQ Sample time: Within 1 week	Package:	1 pair per poly bag, 10 pairs per carton
Amount of load containers: 5000 pairs / container 1x20 ' 10000 pairs / container 1x40 ' 11000 pairs / HQ container 1x40 ' HQ Sample time: Within 1 week	Carton Size:	59x31x31cm
Amount of load containers: 10000 pairs / container 1x40 ' 11000 pairs / HQ container 1x40 ' HQ Sample time: Within 1 week	G.W./N.W.:	18KGS/ 16KGS
The Property of the Control of the C	Amount of load containers:	10000 pairs / container 1x40 '
Sample charge: one pair sample is free, customer need to pay the freight charge.	Sample time:	Within 1 week
	Sample charge:	one pair sample is free, customer need to pay the freight charge.

BBA ankle **PVC** safety shoes:



Inection machine:



Automatic Injection Molding Machine



Puncture Testing Machine



Impact Resistant Testing Machine



Tensile testing machine

CE certificate:

