

YBA steel toe pvc safety rain shoes

Product Name:	Have CE certificate steel toe pvc safety rain shoes for men
Item No:	YBA
Color:	Yellow upper with black sole
Size:	38-46 (4-12)
Average weight:	1.8 kgs/pr (with steel toe and steel plate)
material:	PVC upper and PVC sole
Lining:	Easily dried polyester
Construction:	PVC injection
Standard	Meet CE EN ISO 20345 standard (with steel toe and steel plates)
Steel Toe Protection	Meet 200 Joule
Steel Toe Protection	Meet 1500 Newton
Puncture Resistant	Meet 1100 Newton
Characteristics	1. Water / Acid / Alkali / oil / grease resistant, non-slip, anti-static rubber boots. 2. Steel toe can be Impact & amp; compression resistant. 3. steel plate can be puncture resistant. 4. outsole is abrasion resistant and Contract. 5. Ankle protection, energy absorption on the heel seat region, strengthening toe and heel 6. resistant at low temperatures.
Guarantee:	5 months, robust and solid quality.
Package:	1 pair per poly bag, 10 pairs per carton
Carton Size:	59x31x31cm
G.W./N.W.:	18KGS/ 16KGS
Amount of load containers:	5000 pairs / container 1x20 ' 10000 pairs / container 1x40 ' 11000 pairs / HQ container 1x40 ' HQ
Sample time:	Within 1 week
Sample charge:	one pair sample is free, customer need to pay the freight charge.

YBA ankle rain shoes:



Inection machine:



**Automatic Injection
Molding Machine**



**Puncture
Testing Machine**



**Impact Resistant
Testing Machine**



**Tensile
testing machine**

CE certificate:

EC Type Examination Certificate



Approved Body 0362

The safety footwear detailed herein meets the criteria of an EC Type Examination in accordance with Article 10 of the PPE Directive (89/685/EEC) including amendments and corrigendum up to 14/12/2010 for intermediate design category products.

This has been shown through satisfactory testing to EN ISO 20345: 2011 and examination of the Technical File Documentation.

Following an EC Declaration of Product Conformity you are hereby licensed to mark the product(s) detailed in accordance with Article 13 of the PPE Directive (89/685/EEC).

ITS Testing Services (UK) Ltd
Centre Court
Meridian Business Park
Leicester, LE19 1WD
United Kingdom
Phone: +44 (0)116 263 0330
Fax: +44 (0)116 263 0311



www.intertek.com

Issued to	: HARBIN ANA SAFETY PRODUCTS MFG. CO., LTD. LIXIN VILLAGE, XINHUA TOWN, ACHENG DISTRICT, HARBIN, HEILONGJIANG PROVINCE, CHINA	
Authorised Representative	: HEILONGJIANG SAFER CO., LTD. RM502 PUFA PLAZA, NO. 209 CHANGJIANG RD., HARBIN, CHINA	
Manufacturer	: HARBIN ANA SAFETY PRODUCTS MFG. CO., LTD. LIXIN VILLAGE, XINHUA TOWN, ACHENG DISTRICT, HARBIN, HEILONGJIANG PROVINCE, CHINA	
Date of Issue	: 26 May 2015	
Expiry Date	: 26 May 2020	
Certificate No.	: LEC FI00348759	
Product Reference(s)	: BBA (FW45) SAFETY BOOTS	
Description	Construction	: INJECTION
	Toecap	: 459 STEEL TOECAP
	Midsole	: OY# 160 STEEL PLATE
	Last	: HA-459
	Sole	: PVC & NITRILE
	Mould	: HA-A
	Test Report(s)	: GZHT90504071, GZHT90391794
	Size Range	: EUR 38-47
	Category	: S5 SRA

Carroll
Authorised

26/05/2015

Date

P. Williams
Certification Manager

26/05/2015

Date

For and on behalf of ITS Testing Services (UK) Limited

Registered in England No. 1107024 Registered Office: Academy Place, 1-3 Brook Street, Bournemouth, Dorset, BH1 1TQ

This certificate is for the exclusive use of Intertek's Client and is provided pursuant to the Distribution Agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party other than to the Client in accordance with the agreement. For any loss, damage or personal consequence to the use of this Certificate, only the Client is authorised to permit copying or reproduction of this Certificate and then only in its entirety. Use of Intertek's Certificate when it is restricted to the certificate set out in this agreement and in this Certificate. Any further use of the Intertek name for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek.

