

GYA yeşil ayak bileği pvc çalışma yağmur çizmeleri ile ayak parmakları

Ürün adı:	Çelik ayak ile CE sertifikalı ayak bileği pvc çalışma yağmur botları var mı?
Eşya yok:	GYA
Cenk:	Sarı taban ile yeşil üst
Boyut:	38-46 (4-12)
Ortalama ağırlık:	1,8 kgs / pr (çelik parmak ve çelik plaka ile)
malzeme:	PVC üst ve PVC taban
Astar:	Kolayca kurutulan polyester
İnşaat:	PVC enjeksiyon
Standart	CE EN ISO 20345 standardına uygun (çelik ayak ve çelik plakalar ile)
Çelik Toe Koruma	200 Joule'la tanışın
Çelik Toe Koruma	1500'le tanışın Newton
Delinmeye dirençli	1100'le tanışın Newton
Özellikleri	1. Su / Asit / Alkali / yağ / grese dayanıklı, kaymayan, anti-statik lastik çizme. 2. Çelik parmak Impact & & sıkıştırmaya karşı dayanıklı. 3. Çelik plaka delinmeye dirençli olabilir. 4. dış taban aşınmaya ve Sözleşmeye dirençlidir. 5. Ayak bileği koruması, topuk bölgesi bölgesine enerji emilmesi, parmak ve topuğun güçlendirilmesi 6. Düşük sıcaklıklarda dayanıklıdır.
Garanti:	5 ay, sağlam ve sağlam bir kalite.
Paket:	Poli torba başına 1 çift, karton başına 10 çift
Karton boyutu:	59x31x31cm
G.W./N.W .:	18KGS / 16KGS
biryük konteynerleri:	5000 çift / konteyner 1x20 ' 10000 çift / konteyner 1x40 ' 11000 çift / HQ konteyner 1x40 'Karargah
Örnekleme zamanı:	1 hafta içinde
Örnek ücret:	bir çift numune ücretsiz, müşterinin navlun ücretini ödemesi gerekiyor.

GYA ayak bileği çalışması yağmur botları:



Enfeksiyon makinesi:



**Automatic Injection
Molding Machine**



**Puncture
Testing Machine**



**Impact Resistant
Testing Machine**



**Tensile
testing machine**

CE belgesi:

EC Type Examination Certificate



Approved Body 0362

The safety footwear detailed herein meets the criteria of an EC Type Examination in accordance with Article 10 of the PPE Directive (89/685/EEC) including amendments and corrigendum up to 14/12/2010 for intermediate design category products.

This has been shown through satisfactory testing to EN ISO 20345: 2011 and examination of the Technical File Documentation.

Following an EC Declaration of Product Conformity you are hereby licensed to mark the product(s) detailed in accordance with Article 13 of the PPE Directive (89/685/EEC).

ITS Testing Services (UK) Ltd
Centre Court
Meridian Business Park
Leicester, LE19 1WD
United Kingdom
Phone: +44 (0)116 263 0330
Fax: +44 (0)116 263 0311



www.intertek.com

Issued to	: HARBIN ANA SAFETY PRODUCTS MFG. CO., LTD. LIXIN VILLAGE, XINHUA TOWN, ACHENG DISTRICT, HARBIN, HEILONGJIANG PROVINCE, CHINA	
Authorised Representative	: HEILONGJIANG SAFER CO., LTD. RM502 PUFA PLAZA, NO. 209 CHANGJIANG RD., HARBIN, CHINA	
Manufacturer	: HARBIN ANA SAFETY PRODUCTS MFG. CO., LTD. LIXIN VILLAGE, XINHUA TOWN, ACHENG DISTRICT, HARBIN, HEILONGJIANG PROVINCE, CHINA	
Date of Issue	: 26 May 2015	
Expiry Date	: 26 May 2020	
Certificate No.	: LEC FI00348759	
Product Reference(s)	: BBA (FW45) SAFETY BOOTS	
Description	: Construction	: INJECTION
	: Toecap	: 459 STEEL TOECAP
	: Midsole	: OY# 160 STEEL PLATE
	: Last	: HA-459
	: Sole	: PVC & NITRILE
	: Mould	: HA-A
	: Test Report(s)	: GZHT90504071, GZHT90391794
	: Size Range	: EUR 38-47
	: Category	: S5 SRA

Carroll
Authoriser

26/05/2015

Date

P. Williams
Certification Manager

26/05/2015

Date

For and on behalf of ITS Testing Services (UK) Limited

Registered in England No. 143024 Registered Office: Academy Place, 3-9 Brook Street, Warwick, CV34 7NG

This certificate is for the exclusive use of Intertek's Client and is provided pursuant to the Distribution Agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party other than to the Client in accordance with the agreement. For any loss, expense or damage whatsoever by the use of this Certificate. Only the Client is authorised to permit copying or reproduction of this Certificate and then only in conformity with Intertek's Certificate. It is restricted to the certificate set out in this agreement and in this Certificate. Any further use of the Intertek name for the sale or advertisement of the tested product, provision of services and/or be deemed in writing by Intertek.

